

## NISCA PR-C151 Dual Sided Printer



## **Features**

- Middle Level Printer
- Printing speed 144cards/hr
- 24 bit High Quality and High Reliability



## **Product Specifications**

PR-C151		
Print	Print Method	Dye-sublimation direct printing
	Resolution	300DPI
	Input	R/G/B 256 level
	Output	Y/M/C 256 level
	Printing area	edge to edge
Speed	Printing speed (Single printing: YMCK)	More than 24.0s full color YMCK (144 cards/hr)
	Printing speed (Monochrome printing K)	More than 5.6s full color K (600 cards/hr)
Capacity	Feeder capacity	100 cards (if card thickness is 0.76mm)
	Card exit capacity	100 cards (if card thickness is 0.76mm)
Card	Card thickness	10 mil~50 mil (0.25mm~1.27mm)
	Card size	CR80 : 85.6 x 54cm
	Card material	PVC, PVC composite,
Display	Display	LCD Panel (with back light), LED, Operation button
Size	Dimensions	16.57(H) x 10.66(W) x 13.03(D) Inches (421(H) x 271(W) x 331(D)mm)
	Weight	Less than 26.61 lbs. (13kg)
Power	Power Source	90 - 125VAC 220 - 240VAC 50/60Hz
	Power consumption	Less than 120 W
Temperature	Operating temperature	15 to 35°C - 20 to 80% humidity
Drivers	I/F	USB, Ethernet
	Drivers	XP, Vista, Win 7, Win 8 (32 & 64 bits), Win8.1
Ribbon	Ribbon capacity	250 images / roll (YMCKO ribbon)
	Ink Ribbon	YMCKO, K, YMCFK, KO
Agency Listing	Agency listing	UL/CSA/CE/FCC
Life	MTBF	100,000 prints
	Warranty	2years
Other	Memory size	32MB
Options	Encoder	Mag Encoder / Contact IC Encoder
		Contactless Encoder (Mifare, Legic, HID Prox, iCLASS)
		-

<sup>\*</sup>Specifications subject to change without notice \*\* Contact Team NiSCA for details..



